## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 4 November 2004 (04.11.2004)

**PCT** 

(10) International Publication Number WO 2004/095886 A1

(51) International Patent Classification7: H05B 6/66, 6/68

(21) International Application Number:

PCT/JP2004/005727

(22) International Filing Date: 21 April 2004 (21.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-117073 22 April 2003 (22.04.2003) JP 2003-117072 22 April 2003 (22.04.2003) JP

- (71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO. LTD. [JP/JP]; 1006 Oaza Kadoma Kadoma-shi Osaka, 5718501 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SUENAGA, Haruo. MORIYA, Hideaki. SAKAI, Shinichi.


- (74) Agents: OGURI, Shohei et al.; Eikoh Patent Office 13th Floor ARK Mori Building, 12-32 Akasaka 1-chome, Minato-ku, Tokyo, 1076013 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

[Continued on next page]

(54) Title: HIGH-FREQUENCY DIELECTRIC HEATING DEVICE AND PRINTED BOARD WITH THERMISTOR



(57) Abstract: The present invention provides a high-frequency dielectric heating device comprises: a microwave output unit including an inverter unit using a semiconductor switching element, heat-radiating fins for radiating the heat generated by an IGBT, a printed board having a thermistor for detecting the temperature of the semiconductor switching element, wherein the thermistor being soldered to a leg portion of the semiconductor switching element or near to the leg portion thereof on the side of the soldering surface of the printed board, a booster transformer, a high-voltage rectifier unit, and a magnetron; and a heat-cooking chamber fed with microwaves radiated from the magnetron. When the thermistor has assumed a predetermined resistance, a power-down control operation is effected by greatly decreasing the power fed to the semiconductor switching element. Then, permitting the power fed to the semiconductor switching element to vary depending upon the resistance of the thermistor.



٣,

## WO 2004/095886 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.